











OREGON PU P EST ANTISTATICO 911196



POLYURETHANE (PU) POLYESTER hose with rigid PVC spiral, copper strand for antistatic rendering, for suction and transport of abrasive materials and dry foodstuffs.

DETAILS

	SMOOTH SURFACE	****
	FLEXIBILITY	***
	ABRASION RESISTANCE	*****
	TEMPERATURE RANGE	-25 °C 85 °C
	CHEMICAL RESISTANCE	PU Table
	CRUSHING RESISTANCE	****
	OZONE RESISTANCE	*****
	ANTISTATIC	Strand resistance 0.075 Ohm/m

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23 °C bar	vacuum 23 °C m/H ₂ O	bursting press. at 23 °C bar	bending radius mm	total thickness mm	wall thickness mm	Ø rigid spiral (AxB if oval) mm	Strand Wire in 1 mt m	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
40		40	47	0.4	3	1.2	80	3.5	0.7	3.2	16.5	8.3	right	420	20	In stock
50	2	50	58	0.4	3	1.2	100	4	0.8	3.4	17	10.5	right	550	20	In stock
57		57	65.6	0.4	3	1.2	120	4.3	0.8	4	17.5	11	right	600	20	In stock
60		60	69	0.4	3	1.2	120	4.5	0.8	4.2	18	11.3	right	630	20	In stock
70		70	80	0.3	3	0.9	140	5	0.9	4.5	18	12	right	850	20	In stock
76	3	76.2	86.2	0.3	3	0.9	150	5	0.9	4.5	21	12.3	right	900	20	On demand
80		80	90.5	0.3	3	0.9	160	5.3	0.9	4.8	19	14	right	950	20	In stock
90	3 1/2	90	101	0.2	3	0.6	180	5.5	0.9	5	21	14.5	right	1050	20	On demand
100		100	111	0.2	3	0.6	200	5.5	1	5.1	24	15	right	1150	20	On demand

All technical specifications apply to a temperature of 23° C ± 2° C (ISO 291)

The tolerance on all specifications ±5% (Tolerance Percentage is applicable on ALL DATA across our range)