


DIN 3016 P-Clip Form D



DIN 3016 Rubber lined P-Clips are manufactured from steel strips lined with EPDM rubber. This rubber liner ensures a safe tight-fitting assembly, protects the application area and prevent possible damage caused by vibration. The screw holes are reinforced with metal plates to guarantee a solid grip. P-Clips are recommended for fastening pipes, hoses and conduits in many different applications.

Article	Part n° W1	Part n° W4	Application Ø	Bandwidth a	d	For metric screw	Box Quantity (MOQ)	Outer Packing
AGD 5/12	0300385-6	4300385-9	5	12	5,3	M.5	500	500
AGD 6/12	0300386-4	4300386-7	6	12	5,3	M.5	500	500
AGD 8/12	0300388-0	4300388-3	8	12	5,3	M.5	500	500
AGD 10/12	0300390-1	4300390-4	10	12	5,3	M.5	500	500
AGD 12/12	0300392-8	4300392-0	12	12	5,3	M.5	500	500
AGD 13/12	0300393-6	4300393-9	13	12	5,3	M.5	500	500
AGD 14/12	0300394-4	4300394-7	14	12	5,3	M.5	500	500
AGD 15/12	0300395-2	4300395-5	15	12	5,3	M.5	500	500
AGD 16/12	0300396-0	4300396-3	16	12	5,3	M.5	200	200
AGD 17/12	0300397-9	4300397-1	17	12	5,3	M.5	200	200
AGD 18/12	0300398-7	4300398-0	18	12	5,3	M.5	200	200
AGD 19/12	0300399-5	4300399-8	19	12	5,3	M.5	200	200
AGD 20/12	0300400-7	4300400-0	20	12	5,3	M.5	200	200
AGD 21/12	0300401-5	4300401-8	21	12	5,3	M.5	200	200
AGD 22/12	0300402-3	4300402-6	22	12	5,3	M.5	200	200
AGD 23/12	0300403-1	4300403-4	23	12	5,3	M.5	200	200
AGD 24/12	0300404-0	4300404-2	24	12	5,3	M.5	200	200
AGD 25/12	0300405-8	4300405-0	25	12	5,3	M.5	200	200
AGD 26/12	0300406-6	4300406-9	26	12	5,3	M.5	200	200
AGD 27/12	0300407-4	4300407-7	27	12	5,3	M.5	200	200
AGD 28/12	0300408-2	4300408-5	28	12	5,3	M.5	200	200
AGD 6/15	0300466-4	4300466-7	6	15	6,4	M.6	500	500
AGD 8/15	0300468-0	4300468-3	8	15	6,4	M.6	500	500
AGD 10/15	0300470-1	4300470-4	10	15	6,4	M.6	500	500
AGD 12/15	0300472-8	4300472-0	12	15	6,4	M.6	250	250
AGD 13/15	0300473-6	4300473-9	13	15	6,4	M.6	250	250
AGD 14/15	0300474-4	4300474-7	14	15	6,4	M.6	250	250
AGD 15/15	0300475-2	4300475-5	15	15	6,4	M.6	250	250
AGD 16/15	0300476-0	4300476-3	16	15	6,4	M.6	250	250
AGD 17/15	0300477-9	4300477-1	17	15	6,4	M.6	250	250
AGD 18/15	0300478-7	4300478-0	18	15	6,4	M.6	250	250
AGD 19/15	0300479-5	4300479-8	19	15	6,4	M.6	250	250
AGD 20/15	0300480-8	4300480-0	20	15	6,4	M.6	100	100
AGD 21/15	0300481-6	4300481-9	21	15	6,4	M.6	100	100
AGD 22/15	0300482-4	4300482-7	22	15	6,4	M.6	100	100
AGD 23/15	0300483-2	4300483-5	23	15	6,4	M.6	100	100
AGD 25/15	0300485-9	4300485-1	25	15	6,4	M.6	100	100
AGD 26/15	0300486-7	4300486-0	26	15	6,4	M.6	100	100

Article	Part n° W1	Part n° W4	Application Ø	Bandwidth a	d	For metric screw	Box Quantity (MOQ)	Outer Packing
AGD 28/15	0300488-3	4300488-6	28	15	6,4	M.6	100	100
AGD 30/15	0300490-4	4300490-7	30	15	6,4	M.6	100	100
AGD 32/15	0300492-0	4300492-3	32	15	6,4	M.6	100	100
AGD 34/15	0300494-7	4300494-0	34	15	6,4	M.6	100	100
AGD 35/15	0300495-5	4300495-8	35	15	6,4	M.6	100	100
AGD 37/15	0300497-1	4300497-4	37	15	6,4	M.6	100	100
AGD 38/15	0300498-0	4300498-2	38	15	6,4	M.6	100	100
AGD 40/15	0300500-0	4300500-2	40	15	6,4	M.6	50	50
AGD 10/20	0300710-1	4300550-7	10	20	8,4	M.8	200	200
AGD 11/20	0300551-0	4300551-2	11	20	8,4	M.8	100	100
AGD 12/20	0300552-8	4300552-0	12	20	8,4	M.8	100	100
AGD 13/20	0300553-6	4300553-9	13	20	8,4	M.8	100	100
AGD 14/20	0300554-4	4300554-7	14	20	8,4	M.8	100	100
AGD 15/20	0300555-2	4300555-5	15	20	8,4	M.8	100	100
AGD 16/20	0300556-0	4300556-3	16	20	8,4	M.8	100	100
AGD 17/20	03005562	4300556-8	17	20	8,4	M.8	100	100
AGD 18/20	0300557-9	4300557-1	18	20	8,4	M.8	100	100
AGD 19/20	0300558-7	4300558-0	19	20	8,4	M.8	100	100
AGD 20/20	0300559-5	4300559-8	20	20	8,4	M.8	100	100
AGD 21/20	0300560-8	4300560-0	21	20	8,4	M.8	100	100
AGD 22/20	0300561-6	4300561-9	22	20	8,4	M.8	100	100
AGD 23/20	0300562-4	4300562-7	23	20	8,4	M.8	100	100
AGD 24/20	0300563-2	4300563-5	24	20	8,4	M.8	100	100
AGD 25/20	0300564-0	4300564-3	25	20	8,4	M.8	100	100
AGD 27/20	0300566-7	4300566-1	27	20	8,4	M.8	100	100
AGD 28/20	0300567-5	4300567-0	28	20	8,4	M.8	100	100
AGD 30/20	0300569-1	4300569-6	30	20	8,4	M.8	50	50
AGD 32/20	0300571-2	4300571-5	32	20	8,4	M.8	50	50
AGD 34/20	0300573-9	4300573-1	34	20	8,4	M.8	50	50
AGD 35/20	0300574-7	4300574-0	35	20	8,4	M.8	50	50
AGD 36/20	0300575-5	4300575-8	36	20	8,4	M.8	50	50
AGD 38/20	0300577-1	4300577-4	38	20	8,4	M.8	50	50
AGD 40/20	0300579-8	4300579-0	40	20	8,4	M.8	50	50

TECHNICAL INFORMATION	
	MATERIAL W1: GALVANIZED STEEL (DIN 1.0529) W4: STAINLESS STEEL AISI-430
	FINISH W1: GREY-WHITE WITH EPDM RUBBER W4: STAINLESS STEEL
	TEMPERATURE RESISTANCE -40 + 120 °C

