C/. VIC S/N POL. IND. LA FLORIDA 08130 STA. PERPETUA DE LA MOGODA

TEL: 935602400 FAX: 935602626 Web: http://www.espiroflex.com E-mail: info@espiroflex.com

ESPIROCLEAN 80Bar

CHARACTERISTICS

Hose made by extrusion of vinyl materials, reinforced inside with a polyester wire thread, which provides it great resistance to elongation and stretching ruptures.

The material of the inner layer is white and the interlayer and the external layer materials are blue

The formulation fulfils the current European legislation for objects intended to be in contact with food.

Material non toxic, food quality and phthalate-free, according European Regulations EU 1935/2004 and EU 10/2011.

Temperature range between -15°C y +80°C

APPLICATIONS

This hose is used to clean food industrial facilities and restaurants with hot water. Another use is to impulse food liquids at high temperature, even those with fat content.

TECHNICAL DATA

Ø	Ø		SERVICE	BURST	SERVICE	BURST	BENDING
INT.	EXT.	WEIGHT	PRES	PRES	PRES	PRES	RADIUS
mm	mm	g/m	Bar	Bar	Bar	Bar	mm
			23°C	23°C	80°C	80°C	
12	22	325	80	200	40	100	110

Values of pressure given at room temperature at laboratory. 04-03-2024