

# Pneumatic Fittings

made of Brass Plain

- For technology, compressed air, automation, measure, control and regulation technology, welding, etc.

## Pneumatic 1/3-Screwings

### Materials

- Screwings: Brass MS 58 plain


Max. Working Pressure	Thread	Media	
PN 12 bar	ISO 228	Compressed Air, Gas/ Others	10

### Thread stems with parallel male thread and inner cone 37°

Thread connection	Hose connection	L	SW	L1	L2	Bore	Weight	Type No.
G 1/8 m	Hose i.D. 6	37	13	7	25	5	12	T 186 M
G 1/8 m	Hose i.D. 9	37	13	7	25	5	20	T 189 M
G 1/4 m	Hose i.D. 6	39	17	9	25	5	19	T 146 M
G 1/4 m	Hose i.D. 8	39	17	9	25	6	21	T 148 M
G 1/4 m	Hose i.D. 9	39	17	9	25	7	22	T 149 M
G 1/4 m	Hose i.D. 11	39	17	9	25	8	26	T 1411 M
G 1/4 m	Hose i.D. 13	39	17	9	25	8	34	T 1413 M
G 3/8 m	Hose i.D. 6	40	19	10	25	5	25	T 386 M
G 3/8 m	Hose i.D. 8	40	19	10	25	6	27	T 388 M
G 3/8 m	Hose i.D. 9	40	19	10	25	7	28	T 389 M
G 3/8 m	Hose i.D. 11	40	19	10	25	8	33	T 3811 M
G 3/8 m	Hose i.D. 13	40	19	10	25	9,5	36	T 3813 M
G 1/2 m	Hose i.D. 6	40	24	10	25	5	37	T 126 M
G 1/2 m	Hose i.D. 9	40	24	10	25	7	41	T 129 M
G 1/2 m	Hose i.D. 13	40	24	10	25	11	44	T 1213 M
G 3/4 m	Hose i.D. 19	56	27	16	32	13	125	T 3419 TM*
G 1 m	Hose i.D. 25	70	36	17	41	20	210	T 1025 TM*

For hose clips type ZOS (☺ page 130), type HS (☺ page 131) or crimping ferrules type LPH (☺ page 133), Thread sealing with PVC sealing ring type HPD (☺ page 212)

\*without inner cone



## Pneumatic 2/3-Screwings

### Materials

- Screwings: Brass MS 58 plain

Max. Working Pressure	Thread	Media	
PN 12 bar	ISO 228	Compressed Air, Gas/ Others	10

### Hexagon nut

Thread connection	L	SW	Bore	Weight	Type No.
G 1/8 i	12	13	7,2	13	U 18 M
G 1/4 i	14	17	10,6	16	U 14 M
G 3/8 i	15	19	13	15	U 38 M
G 1/2 i	16	24	15,5	28	U 12 M

### Hose Stems with outer cone for hexagon nut

Hose connection	Version for	L	L1	L2	L3	Bore	Weight	Type No.
Hose i.D. 6	U 18 M	40	4	34	28	4	7	ST 186 M
Hose i.D. 6	U 14 M	42	6	34	28	4	12	ST 146 M
Hose i.D. 9	U 14 M	42	6	34	28	5,5	14	ST 149 M
Hose i.D. 6	U 38 M	47	7	38	28	4	23	ST 386 M
Hose i.D. 9	U 38 M	47	7	38	28	6,5	23	ST 389 M
Hose i.D. 11	U 38 M	47	7	38	28	7	30	ST 3811 M
Hose i.D. 6	U 12 M	47	7	38	29	4	32	ST 126 M
Hose i.D. 9	U 12 M	47	7	38	29	6,5	33	ST 129 M
Hose i.D. 13	U 12 M	47	7	38	29	9	34	ST 1213 M

For hose clips type ZOS (☺ page 130), type HS (☺ page 131) or crimping ferrules type LPH (☺ page 133)

