



SBR rubber sheet

Black Miami

Quality:	NR/SBR
Colour:	Black
Temperature range:	-30° to +70°C
Specific gravity:	1,5 grs/cm ³
Hardness:	70 Shore A +/- 5
Tensile strength:	3 Mpa
Elongation at break:	200%

Features: Widely used industrial rubber quality with good mechanical properties, abrasion and shock resistance.

Application: General purpose gaskets, shock absorbers, conveyer belts, insulation et cetera.

Thickness (mm)	Insertion(s) (no.)	Insertion type	Width (mtr)	Length (mtr)	Article nr.
1	0	-	1,4	10/20	SX70150 1/0
1,5	0/1	cotton	1,4/1,2	15	SX70150 1,5/0
2	0/1	cotton	1,4/1,2	10	SX70150 2/0
3	0/1/2	cotton	1,4/1,2	10	SX70150 3/0
4	0/1/2	cotton/EP100	1,4/1,2	10	SX70150 4/0
5	0/1/2	cotton	1,4/1,2	10	SX70150 5/0
6	0/1/2	cotton/EP100	1,4/1,2	10	SX70150 6/0
8	0/2	cotton	1,4/1,2	5/10	SX70150 8/0
10	0/2	cotton	1,4/1,2	5/10	SX70150 10/0
10	0	-	1	1	SX70150 10/0-1x1
12	0	-	1,4	5	SX70150 12/0
15	0	-	1,4	5	SX70150 15/0
15	0	-	1	1	SX70150 15/0-1x1
20	0	-	1,4	5	SX70150 20/0
20	0	-	1	1	SX70150 20/0-1x1
25	0	-	1,4	5	SX70150 25/0
25	0	-	1	1	SX70150 25/0-1x1
30	0	-	1,4	5	SX70150 30/0
30	0	-	1	1	SX70150 30/0-1x1
40	0	-	1	1	SX70150 40/0-1x1
50	0	-	1	1	SX70150 50/0-1x1



Rubber Europe

Thickness Tolerances		
Over (mm)	Upto (mm)	Tolerance +/- (mm)
0.5	2	0.2
2	3	0.3
3	6	0.4
6	10	0.5
10	15	0.8
15	25	1.0

Roll length Tolerances	
Length (mm)	Tolerance +/- (mm)
1.000	50
5.000	250
10.000	500
20.000	1.000

Roll width Tolerances	
length (mm)	Tolerance +/- (mm)
900	18
1.000	20
1.220	24
1.300	26
1.400	28