

ZÁVITOVÁ REDUKCE AG/IG-UP MS - niklované šroubení s vnějším a vnitřním závitem

<http://www.gms.cz/cz/vyrobek/52101>

objednávací kód



52101***

(logistický)

G₁G₂

bar

mm

bar
(max.)

mm

kg/ks

ks



RAGM5-IG18/MS



RAG14-IG38/MS



RAG12-IG34/MS

52101005	RAGM5-IG18/MS-183	M5x0,8 - IG1/8"	16	CH14	40	B12	0,010	1
52101013	RAG18-IG14/MS-183	AG1/8 - IG1/4"	16	CH17	40	B18	0,017	1
52101015	RAG18-IG38/MS-183	AG1/8 - IG3/8"	16	CH19	40	B19	0,030	1
52101017	RAG18-IG12/MS-183	AG1/8 - IG1/2"	16	CH24	40	B22	0,033	1
52101021	RAG14-IG38/MS-183	AG1/4 - IG3/8"	16	CH19	40	B20	0,031	1
52101025	RAG14-IG12/MS-183	AG1/4 - IG1/2"	16	CH24	40	B14	0,050	1
52101029	RAG38-IG12/MS-183	AG3/8 - IG1/2"	16	CH24	40	B16	0,055	1
52101033	RAG12-IG34/MS-183	AG1/2 - IG3/4"	16	CH32	40	B19	0,065	1

Použití: Šroubení pro vodu a vzduch v průmyslu**Normy:** Závity ISO 228**Poznámka:** Kompatibilita RoHs,