

32397



| ZÁVIT 1.<br>(Rp) | ZÁVIT 2.<br>(Rp) | ØD<br>(mm) | CH<br>(mm) | HMOTNOST<br>(kg/ks) | TLAK<br>(bar) | BALENÍ<br>(ks) | OBJEDNACÍ<br>KÓD |
|------------------|------------------|------------|------------|---------------------|---------------|----------------|------------------|
| G 1"             | G 3/8"           | -          | -          | 0,110               | 16            | 1              | RIG10-38/SS-KUL  |
| G 1"             | G 1/2"           | -          | -          | 0,120               | 16            | 1              | RIG10-12/SS-KUL  |
| G 1"             | G 3/4"           | -          | -          | 0,115               | 16            | 1              | RIG10-34/SS-KUL  |
| G 5/4"           | G 1"             | -          | -          | 0,185               | 16            | 1              | RIG54-10/SS-KUL  |
| G 6/4"           | G 1"             | -          | -          | 0,230               | 16            | 1              | RIG64-10/SS-KUL  |
| G 2"             | G 1"             | -          | -          | 0,340               | 16            | 1              | RIG20-10/SS-KUL  |

**Další možné rozměry - redukce závitu:**

|             |             |             |           |
|-------------|-------------|-------------|-----------|
| 1/4" - 1/8" | 1/2" - 1/8" | 3/4" - 1/4" | 2" - 5/4" |
| 3/8" - 1/8" | 1/2" - 1/4" | 5/4" - 1/2" | 2" - 6/4" |
| 3/8" - 1/4" | 1/2" - 3/8" | 5/4" - 3/4" |           |
|             |             | 6/4" - 3/4" |           |
|             |             | 6/4" - 3/4" |           |

**Pracovní teplota:** -40°C až +300°C**Těsnění:** -**Médium:** Voda, vzduch, benzíny, oleje, chemikálie**Poznámka:** Korozi vzdorná ocel DIN 1.4408, EN 10283: 2010