

WORKING PRESSURE COUPLINGS

"Ferrari" type couplings. Female couplings with 2 hooks.

| diam. | Working pressure |
|--------|------------------|
| 48 mm | 10 bars |
| 60 mm | 10 bars |
| 80 mm | 9 bars |
| 100 mm | 8 bars |
| 120 mm | 7 bars |
| 150 mm | 6 bars |

"Ferrari" type couplings. Female couplings with 3 hooks.

| diam. | Working pressure |
|--------|------------------|
| 60 mm | 14 bars |
| 80 mm | 12 bars |
| 100 mm | 11 bars |
| 120 mm | 10 bars |
| 150 mm | 9 bars |

"Anfor" type couplings. Female couplings with 2 hooks.

| diam. | Working pressure |
|--------|------------------|
| 60 mm | 19 bars |
| 80 mm | 16 bars |
| 100 mm | 14 bars |
| 120 mm | 13 bars |
| 150 mm | 12 bars |
| 200 mm | 6 bars |
| 250 mm | 5 bars |
| 300 mm | 5 bars |
| 400 mm | 5 bars |

"Anfor" type couplings. Female couplings with 3 hooks.

| diam. | Working pressure |
|--------|------------------|
| 100 mm | 19 bars |
| 120 mm | 17 bars |
| 150 mm | 16 bars |
| 200 mm | 10 bars |
| 250 mm | 8 bars |
| 300 mm | 8 bars |

"B" type couplings interchangeable with the existing Bauer type.

| diam. | Working pressure |
|-------|------------------|
| 2" | 20 bars |
| 3" | 20 bars |
| 3"1/2 | 20 bars |
| 4" | 12 bars |
| 6" | 12 bars |
| 8" | 12 bars |

"P – Cardan Perrot" type couplings.

| diam. | Working pressure |
|-------|------------------|
| 2" | 20 bars |
| 3" | 20 bars |
| 3"1/2 | 15 bars |
| 4" | 15 bars |
| 6" | 10 bars |