

Rychlospojky (samec) Kamlok

z nerez. oceli 1.4401

Samec s hadicovým nátrubkem dle normy US-MIL

Obj. č.	Typ. velikost	Trn na hadici	DN	h	Ident. rozměr	Hmotnost (g)
50-E-SS	50 = 1/2"	13 mm	15	87	24	120
75-E-SS	75 = 3/4"	19 mm	20	88	32.1	171
100-E-SS	100 = 1"	25 mm	25	103	36.7	284
125-E-SS	125 = 1 1/4"	32 mm	32	110	45.5	442
150-E-SS	150 = 1 1/2"	38/40 mm	40	116	53.4	563
200-E-SS	200 = 2"	50 mm	50	146	63	812
250-E-SS	250 = 2 1/2"	63 mm	65	148	75.8	1186
300-E-SS	300 = 3"	75 mm	80	167	91.5	1815
400-E-SS	400 = 4"	100 mm	100	175	119.5	2945

Ident. rozměr



Samec s vnitřním závitem a těsnícím kroužkem vnitřního závitu DIN EN 14 420-7 Forma AF

Obj. č.	Typ. velikost	Závít	DN	h	Ident. rozměr	Hmotnost (g)
50-A-SS	50 = 1/2"	G 1/2"	15	41	24	76
75-A-SS	75 = 3/4"	G 3/4"	20	42	32.1	171
100-A-SS	100 = 1"	G 1"	25	52	36.7	222
125-A-SS	125 = 1 1/4"	G 1 1/4"	32	58	45.5	386
150-A-SS	150 = 1 1/2"	G 1 1/2"	40	62	53.4	493
200-A-SS	200 = 2"	G 2"	50	71	63	644
250-A-SS	250 = 2 1/2"	G 2 1/2"	65	75	75.8	945
300-A-SS	300 = 3"	G 3"	80	79	91.5	1320
400-A-SS	400 = 4"	G 4"	100	81	119.5	2118



Samec s vnějším závitem DIN EN 14 420-7 Forma FF

Obj. č.	Typ. velikost	Závít	DN	h	Ident. rozměr	Hmotnost (g)
50-F-SS	50 = 1/2"	R 1/2"	15	49	24	103
75-F-SS	75 = 3/4"	R 3/4"	20	64	32.1	185
100-F-SS	100 = 1"	R 1"	25	72	36.7	258
125-F-SS	125 = 1 1/4"	R 1 1/4"	32	81	45.5	477
150-F-SS	150 = 1 1/2"	R 1 1/2"	40	82	53.4	565
200-F-SS	200 = 2"	R 2"	50	90	63	650
250-F-SS	250 = 2 1/2"	R 2 1/2"	65	105	75.8	1317
300-F-SS	300 = 3"	R 3"	80	104	91.5	1766
400-F-SS	400 = 4"	R 4"	100	114	119.5	2804



Záslepka samce DIN EN 14 420-7 Forma DP

Obj. č.	Typ. velikost	DN	h	Ident. rozměr	Hmotnost (g)
50-DP-SS	50 = 1/2"	15	36	24	73
75-DP-SS	75 = 3/4"	20	39	32.1	93
100-DP-SS	100 = 1"	25	46	36.7	139
125-DP-SS	125 = 1 1/4"	32	55	45.5	260
150-DP-SS	150 = 1 1/2"	40	57	53.4	335
200-DP-SS	200 = 2"	50	60	63	441
250-DP-SS	250 = 2 1/2"	65	66	75.8	657
300-DP-SS	300 = 3"	80	66	91.5	804
400-DP-SS	400 = 4"	100	68	119.5	1525

