

WELBLU 20 ISO3821 L/L

WELDING HOSE- OXIGEN



APPLICATION

Delivery hose, oxygen line in welding equipments

TUBE

Black, smooth, **SBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Blue, smooth, **SBR/EPDM** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-13°F +176°F

-25°C +80°C

SPECIFICATIONS

ISO 3821

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
6	1/4	13	1/2	0.16	20	300	60	900	50/100
8	5/16	15	19/32	0.18	20	300	60	900	50/100
9	23/64	16	5/8	0.20	20	300	60	900	50/100
10	3/8	17	43/64	0.21	20	300	60	900	50/100
13	1/2	23	29/32	0.40	20	300	60	900	50/100
16	5/8	26	1 5/16	0.53	20	300	60	900	50/100
19	3/4	30	1 3/16	0.62	20	300	60	900	50/100
25	1	37	1 29/64	0.86	20	300	60	900	50/100

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

TGT WELBLU W.P. 20 BAR ISO 3821 ITALY