

Mortar Couplings

made of Aluminium, Type Size X25, rigid and swivelling



- Couplings made of aluminium, optional rigid or swivelling
- Mainly used at the spraying device
- 60 % weight reduction compared to version made of malleable iron, therefore essentially easier operation in continuous use
- Swivelling version made of three parts, lead in teflon slide, absolutely leakage-proof for long lifetime
- Swivelling version allows permanent floating of mostly rigid mortar hoses for much easier handling in the respective application

Materials

- Coupling: Aluminium
- Handle: Malleable iron zinc-plated and yellow passivated (free of chrome VI)
- Seals: NBR, PTFE, PUR*


Max. Working Pressure	Temperature	Thread	System	TÜV-certified	Media	
PN 40 bar	-40°C – +90°C	ISO 228	X25	all types	Mortar/concrete	1

Couplings with female thread

Thread connection	L	SW	B	Type-Size	ID	L1	Passage	Version	Weight	Type No.
G 1 f	72	41	70	X25	42	19	25	rigid	290	MIG 10-X25A
G 1 f	120	41	70	X25	42	21	23	swivelling	405	MIG 10-X25ADR*

Rubber rings Type No. MDR-X25 and handles Type No. MNH-630 (© page 245)

*Female thread sealing ring made of material polyurethane



swivelling

