



ART. 8288.105

Open hose reels with polyurethane hose

Fixed hose reel, s.288, for air-water, 20 bar, hose PU 15
m ø 6 x 10 mm



FLUIDS

AIR | WATER | NITROGEN/INFLATING USE

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND
ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Pressure	bar	20
Compatible fluids		air - water
Swivel joint		brass
Seals		Viton®
Characteristic		fixed
Material		painted steel
Couplings		brass
Hose		971.015
ø and hose length	ø - m	1/4" - 15
Inlet		G 3/8" (m)
Outlet		G 1/4" (m)
Reel flow path		brass - nylon PA6
Internal drum width	mm	98

RAASM SpA


via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright ® 2020 All rights reserved to RAASM S.p.A.



Overall dimensions



RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.