



GREASE - 400 bar


PAINTED STEEL

Ex ATEX directive
IIB 2 GD c T4 T135 °C X

Supplied with:
- hoses in black synthetic rubber
- zinc plated steel couplings
- carbon steel swivel joint
- "polyurethane" seals



FIXED	
	
Article	
8330.500 *	
8330.501	

SWIVELLING	
	
Article	
-	
-	

Hose supplied	Connection	
	inlet	outlet
without hose	F3/8"G	F3/8"G
12m - 1/4" (993.511)	F3/8"G	M1/4"G



S. 330

S. 390

S. 430

S. 530

S. 540

8390.500 *
8390.501
8390.502

8380.500 *
8380.501
8380.502

8430.500 *
8430.501
8430.502
8430.505
8430.506

8420.500 *
8420.501
8420.502
8420.505
8420.506

without hose
12m - 1/4" (993.511)
16m - 1/4" (993.516)

without hose
12m - 1/4" (993.512)
18m - 1/4" (993.518)
10m - 3/8" (995.710)
15m - 3/8" (995.715)

for ABS hose reels Series 430 see page 152

8530.500 *
8530.501
8530.502

8520.500 *
8520.501
8520.502

without hose
20m - 3/8" (995.720)
25m - 3/8" (995.725)

8540.500 *
8540.501

8550.500 *
8550.501

without hose
30m - 3/8" (995.730)

* 600 bar

* 600 bar

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reels.
The **template** supplied facilitates drilling of the holes and there fore hose reels fixing.

SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reels installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.

