

RED WATER

INDUSTRIAL MAINTENANCE

Water/Cleaning and wash-down



Applications

Water discharge under pressure on industrial or urban sites.

Advantages

- Sturdy hose.
- Good resistance to abrasion thanks to wall thickness.

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, red, smooth for ID ≤ 25 mm, fabric impression for ID > 25 mm.

Temperature range: - 25 °C to + 70 °C.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Price €/m
13.0	4	21	10	30	78	0.36	40	Consult
16.0	4	24	10	30	96	0.43	20 - 40	Consult
19.0	4.5	28	10	30	115	0.56	20 - 40	Consult
25.0	5	35	10	30	150	0.80	20 - 40	Consult
32.0	5.5	43	10	30	200	0.90	40	Consult
38.0	6	50	10	30	210	1.00	40	Consult
45.0	6.5	58	10	30	330	1.35	40	Consult
51.0	7	65	10	30	400	1.60	40	Consult
57.0	7	71	10	30	570	1.65	40	Consult
63.0	7	77	10	30	630	1.75	40	Consult
76.0	8	92	10	30	750	2.00	40	Consult
89.0	8	105	10	30	900	2.25	40	Consult
100.0	8	116	10	30	1000	3.20	40	Consult
114.0	8	130	10	30	1200	3.33	40	Consult
127.0	8.5	144	10	30	1300	3.92	40	Consult
152.0	9	170	10	30	1600	4.93	40	Consult

Length in blue = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

TRELLEBORG

RED WATER

TRELLEBORG