

Feuerschutzschlauch - EN45545 / DIN5510-2

Fire protection hose - EN45545 / DIN5510-2

Tuyau de protection contre l'incendie - EN45545 / DIN5510-2

Funda de protección contra incendios - EN45545 / DIN5510-2

Wąż przeciwpożarowy - EN45545 / DIN5510-2

Protezione antifiama per tubi - EN45545 / DIN5510-2

**NEW**

Part-No.	 mm	 mm	 bar	 mm	 %	 g/m	Price/m
SSCF-10B	10	13,2					
SSCF-15B	15	19,2					
SSCF-20B	20	24,6					
SSCF-22B	22	27					
SSCF-25B	25	30,2					
SSCF-30B	30	35,8					
SSCF-32B	32	38					
SSCF-35B	35	41,2					
SSCF-40B	40	46,8					
SSCF-50B	50	57,4					

Beschreibung:	Silikonbeschichtetes Fiberglas
Betriebstemperatur:	max 260°C kurzfristig 1100°C
Norm:	EN45545 und DIN5510-2 UL 1441
Rollenware:	20m (kein Anschnitt)
Desription:	Silicone coated fiberglas
Temperature:	max 260°C short time 1100°C
Norm:	EN45545 and DIN5510-2 UL 1441
Coil:	20m (no short lengths available)