



MESSAGE NUMBER 620909 / 2014

Copy sent to (60866) GMS VELKOOBCHOD S.R.O.

NUMBER to mention in the incoming correspondence: 23818.14 dated APR/24/14

IVG, 24/04/2014

FAX FOR GMS Velkoobchod s.r.o.

REF.: Enquiry - BOSCH

We thank you for your a.m. inquiry and we offer as follows:

AUTO YORK SPEC/20

softwall hose for conveying closed-circuit cooling water mixed with fat residues of oil and suitable also for Waterdos SIM 28 protective agent and Waterdos CIT 48 biocide agent.

Tube: black, smooth, synthetic conductive rubber.

Reinforcement: high strength synthetic cord.

Cover: black, smooth (wrapped finish), conductive and auto-extinguishing synthetic rubber, weathering, abrasion, ozone and oil resistant.

Temperature: from -20°C up to +80°C

Electrical resistance: Ohm/T, electrically conductive hose.

Working pressure: 20 bar      Safety Factor: 3:1

Quant	Diam/mm	Weight
1x120m	13x24	0,38 Kg/m
1x120m	19x30	0,51 Kg/m
1x120m	25x37	0,67 Kg/m

REMARKS  
\*\*\*\*\*

After a check with our R&D dept. and thanks to your great cooperation we are proposing you our best solution for BOSCH enquiry.

Please take note that we have no experience about the application required, so it would be better if BOSCH will have the possibility to test a trial order and send us a complete and detailed report to better understand if everything is ok.

From our side we can confirm that the a/m product is suitable for the working condition required and for the fluids stated in your message dated 08/04.

