


GTH

ISO 4079 R6



-size	DN	"	"	mm	PSI	MPa	PSI	MPa	mm	mm/Hg	kg/100m	REF.
-4	6	1/4	0.50	12.7	400	2.8	1600	11.2	65	710	13	4GTH
-5	8	5/16	0.56	14.3	400	2.8	1600	11.2	75	710	15	5GTH
-6	10	3/8	0.63	15.9	400	2.8	1600	11.2	75	710	17	6GTH
-8	12	1/2	0.78	19.8	400	2.8	1600	11.2	100	450	23	8GTH
-10	16	5/8	0.91	23.0	350	2.4	1400	9.6	125	380	28	10GTH
-12	19	3/4	1.06	26.9	300	2.1	1200	8.4	150	380	38	12GTH
-16	25	1	1.32	33.5	250	1.7	1000	6.9	165	250	47	16GTH

**RECOMMENDED FOR**

High temperature, low pressure hydraulic oil lines, heavy-duty transmission oil cooler lines and glycol anti-freeze solutions.

**TUBE**

NBR (Nitrile) based.

**REINFORCEMENT**

One fibre braid.

**COVER**

CR (Chloroprene) based.

**TEMPERATURE RANGE**

-40°C to +135°C constant and +150°C intermittent. For water emulsions, etc. see page 86.

**STANDARDS**

EN 854 R6. SAE 100R6. ISO 4079 R6 - high temperature.

**COUPLINGS**

MegaCrimp®.