



CERTIFICATE OF CONFORMITY

PETROSPIR S&D /16 - EN12115

FUEL AND MINERAL OIL SUCTION AND DELIVERY HOSE ACCORDING TO EN 12115

APPLICATION : SUCTION & DELIVERY HOSE SUITABLE FOR PETROLEUM BASED PRODUCTS WITH AN AROMATIC CONTENT UP TO 50%

HOSE LINER : BLACK NBR RUBBER COMPOUND

HOSE REINFORCEMENT : HIGH TENACITY SYNTHETIC YARNS WITH STEEL SPIRAL EMBEDDED. THE ELECTRICAL CONTINUITY IS ASSURED BY A COPPER WIRE

HOSE COVER : BLACK, SMOOTH, CLOTH IMPRESSION CR ANTISTATIC RUBBER (R<10⁶ ohm/m), RESISTANT TO OIL, FUEL, ABRASION & ATMOSPHERIC AGENTS

SPECIFICATIONS : EN12115

WORKING TEMPERATURE -30°C + 80°C - (-22°F +176°F)

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	LENGHT
mm	inch	mm	inch	Kg/m	bar	psi	bar	psi	mm	MAX m
19,0	3/4	31,0	1.7/32	0,70	16	240	64	960	125	40 / 61
25,0	1	37,0	1.29/64	0,90	16	240	64	960	150	40 / 61
32,0	1.1/4	44,0	1.47/64	1,20	16	240	64	960	175	40 / 61
38,0	1.1/2	51,0	2	1,50	16	240	64	960	225	40 / 61
51,0	2	67,0	2.41/64	2,30	16	240	64	960	275	40 / 61
63,5	2.1/2	80,0	3.5/32	2,80	16	240	64	960	300	40 / 61
76,0	2	92,0	3.5/8	3,30	16	240	64	960	350	40 / 61
102,0	4	118,0	4.41/64	4,70	16	240	64	960	450	40 / 61

7/04/2010
TUBI GOMMA TORINO
 Garanzia e Qualità