

## INFINITY™ FUEL DROP HOSE



**NEW**

### Product Specifications

- APPLICATION:** Constructed with the exclusive PVC double helix for superior flexibility, abrasion resistance and low coefficient of friction for ease of maneuverability. Lightweight in construction, it is designed to transfer biodiesel and ethanol blends, gasoline and other petroleum products under pressure, gravity flow or medium suction (up to 23° Hg) at ambient temperature and with an aromatic content of 60% or less.
- CONSTRUCTION TUBE:** Black Nitrile synthetic rubber (static dissipating).
- COVER:** Black Chemivic™ synthetic rubber with orange & green Pliovic® outer helix.
- REINFORCEMENT:** Synthetic fabric plies with static wire.
- TEMPERATURE:** -40°F to 160°F (-40°C to 71°C)
- PACKAGING:** Coiled and polywrapped. For cut length, check with your Goodyear Engineered Products distributors.
- BRANDING:** Example: Infinity™ Drop Hose Goodyear®.
- COUPLINGS:** Use Goodyear Engineered Products Insta-Lock™ Cam & Groove Fittings with this product.
- ORDER CODES:** 543-773

AIR &  
MULTIPURPOSE  
General Purpose  
Heavy Duty  
Push-on

CHEMICAL  
TRANSFER

CLEANING  
EQUIPMENT

FOOD  
Transfer  
Washdown

MARINE

MATERIAL  
HANDLING  
Abrasives  
Bulk Transfer  
Cement & Concrete

MINING

PETROLEUM  
Aircraft Fueling  
Dispensing  
Dock  
Transfer

SPRAY

STEAM

VACUUM

VEYANCE

WATER  
Discharge  
Suction &  
Discharge  
Washdown

WELDING

COUPLING  
SYSTEMS

APPENDIX

### INFINITY™

ID		NOM. OD		MAX. WP		BEND RADIUS		VACUUM HG		WEIGHT	
in.	mm.	in.	mm.	psi	Mpa	in.	mm.	in.	mm.	lb./ft.	kg./m.
2	51.0	2.80	70.50	150	1.03	1.5	1.02	23	584	1.02	1.52
3	76.0	3.80	95.48	100	.69	2.0	1.46	23	584	1.46	2.18
4	102.0	4.80	121.47	75	.52	2.5	1.73	23	584	1.73	2.57