

# PERFORMER CERAMIC



## CONSTRUCTION & MINING EQUIPMENT

Abrasive materials hydraulic and pneumatic handling



### APPLICATIONS

Hydraulic suction or discharge of highly abrasive material.

### ADVANTAGES

- | At least 10 times longer lifespan compared to a rubber hose.
- | 4 to 5 times more flexible than market standard ceramic hoses.
- | Quick and easy installation:
  - | Hoses can be cut to length on site without specific toolings.
  - | Very easy BLOC-END® coupling installation.
  - | 30 to 60% lighter weight compared to market standard ceramic hoses.

### TECHNICAL DESCRIPTION

Inner tube: Al2O3,92% ceramic tiles embedded into a NR tube, black.

Reinforcement: synthetic textile with embedded steel helix.

Cover: weather resistant EPDM, black, corrugated, fabric impression.

Temperature range: -30 °C to +70 °C.

### COUPLINGS/FITTINGS

Hoses are fitted with BLOC-END® and must be used to the following maximum working pressure:

ID ≤ 150mm: 10bar,

ID > 150mm:

10bar for static application (no hose movement, no water hammer, no traction) and/or temperature max < 40 °C, 5bar for dynamic application and/or temperature > 40 °C.

### COMPLEMENTARY INFORMATION

Hoses are manufactured and delivered in custom length.



**CONSTRUCTION & MINING  
EQUIPMENT****PERFORMER CERAMIC**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	MAX. LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
50.0	83.0 ±2	10	30	0.9	200	4.8	10	5606036	10
65.0	98.0 ±2	10	30	0.9	300	5.8	10	5606037	∞
80.0	113.0 ±2	10	30	0.9	350	6.7	10	5606038	∞
100.0	133.0 ±2	10	30	0.9	400	8.2	10	5606039	10
125.0	158.0 ±2	10	30	0.9	600	10.1	10	5606040	∞
150.0	183.0 ±2	10	30	0.9	700	11.9	10	5606041	∞
200.0	234.5 ±2	10	30	0.9	1300	16.7	10	5606042	∞

Tolerance on length: ±1% (ISO 1307 Standard).

∞ Upon availability.

**TRELLEBORG**



# PERFORMER CERAMIC

## CONSTRUCTION & MINING EQUIPMENT

### Abrasive materials hydraulic and pneumatic handling

Hydraulic suction or discharge of highly abrasive material.

#### Advantages

- At least 10 times longer lifespan compared to a rubber hose.
- 4 to 5 times more flexible than market standard ceramic hoses.
- Quick and easy installation:
  - Hoses can be cut to length on site without specific toolings.
  - Very easy BLOC-END® coupling installation.
  - 30 to 60% lighter weight compared to market standard ceramic hoses.

### Technical description

**Inner tube:** Al2O3,92% ceramic tiles embedded into a NR tube, black.

**Reinforcement:** synthetic textile with embedded steel helix.

**Cover:** weather resistant EPDM, black, corrugated, fabric impression.

**Temperature range:** -30°C to +70°C.

### Couplings/Fittings

Hoses are fitted with BLOC-END® and must be used to the following maximum working pressure:

ID ≤ 150mm: 10bar,

ID > 150mm:

10bar for static application (no hose movement, no water hammer, no traction) and/or temperature max <40°C,  
5bar for dynamic application and/or temperature >40°C.

### Complementary information

Hoses are manufactured and delivered in custom length.

ID mm	OD mm		Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Max. length m	Article number	Stock (●) or min. order m
50.0	83.0	±2	10	30	0.9	200	4.80	10	5606036	10
65.0	98.0	±2	10	30	0.9	300	5.80	10	5606037	□
80.0	113.0	±2	10	30	0.9	350	6.70	10	5606038	□
100.0	133.0	±2	10	30	0.9	400	8.20	10	5606039	10
125.0	158.0	±2	10	30	0.9	600	10.10	10	5606040	□
150.0	183.0	±2	10	30	0.9	700	11.90	10	5606041	□
200.0	234.5	±2	10	30	0.9	1300	16.70	10	5606042	□

□ Upon availability.

Tolerance on length: ±1% (ISO 1307 Standard).

