



# Espiroflex

FÁBRICA DE TUBERÍA FLEXIBLE

C/. VIC S/N POL. IND. LA FLORIDA 08130 STA. PERPETUA DE LA MOGODA

TEL: 935602400 FAX : 935602626 Web: <http://www.espiroflex.com> E-mail : [info@espiroflex.com](mailto:info@espiroflex.com)

## TRANSAIR M

### CHARACTERISTICS

Tube made from flexible PVC with rigid spiral, practically non deformable and anti-choke.

The inner surface is smooth while the exterior one is corrugated.

Great flexibility (bending radius equal to interior diameter) and lightness.

Resistant to impacts, atmospheric agents, to smoke and to a wide range of chemical products.

Temperature range between  $-15^{\circ}\text{C}$  and  $65^{\circ}\text{C}$

### USAGE

Aspiration and impulsion of fumes, shavings, seeds, textile fibres, etc, where protection from fire is necessary.

Industrial aspiration and ventilation

### TECHINICAL DATA

Ø INT. mm	WALL mm	WEIGH T g/m	VACUUM m H <sub>2</sub> O	BENDING RADIUS mm
13	2.1	90	5	13
14	2.1	95	5	14
16	2.3	104	5	16
20	2.5	130	5	20
25	2,6	170	5	25
32	3,0	250	5	32
38	3,1	325	5	38
40	3,2	340	4	40
50	3,5	450	4	50

01-12-2010