



NBR rubber sheet

Satyr Medium

Quality:	NBR/SBR
Colour:	Black
Temperature range:	-25° to +80°C
Specific gravity:	1,45 grs/cm ³
Hardness:	70 Shore A +/- 5
Tensile strength:	5 Mpa
Elongation at break:	250%

Features: Widely used oil and grease resistant industrial rubber quality with good mechanical properties. Resistant to gasoline, oil, propane, natural gas and coal gas.

Application: Chemical industries, garages, workshops et cetera.

Thickness (mm)	Insertion(s) (no.)	Insertion type	Width (mtr)	Length (mtr)	Article nr.
1	0	-	1,2/1,4	20	NB70140 1/0
1,5	0	-	1,4	15	NB70140 1,5/0
2	0/1	nylon	1,2/1,4	10	NB70140 2/0
3	0/1/2	nylon	1,2/1,4	10	NB70140 3/0
4	0/2	nylon	1,2/1,4	10	NB70140 4/0
5	0	-	1,2/1,4	10	NB70140 5/0
6	0	-	1,4	10	NB70140 6/0
8	0	-	1,4	5	NB70140 8/0
10	0	-	1,4	5	NB70140 10/0



Rubber Europe

Thickness Tolerances		
Over (mm)	Upto (mm)	Tolerance +/- (mm)
0.5	2	0.2
2	3	0.3
3	6	0.4
6	10	0.5
10	15	0.8
15	25	1.0

Roll length Tolerances	
Length (mm)	Tolerance +/- (mm)
1.000	50
5.000	250
10.000	500
20.000	1.000

Roll width Tolerances	
length (mm)	Tolerance +/- (mm)
900	18
1.000	20
1.220	24
1.300	26
1.400	28