



## NR high quality rubber

### Red Dragoon

Colour: red

Finish: one side smooth, one side fabric finish

Temperature range: -40° to +70°C

**Features:** a soft and highly elastic rubber with excellent mechanical properties.

- Resistant to all non-oxidizing acids.
- Not weather resistant

**Application:** very wide range of applications, s.a conveyor systems, pumps, etc

		Test method
Specific gravity grs/cm <sup>3</sup>	0,98	DIN 53508
Hardness shore A ± 5°	38	DIN 53505
Tensile strength Mpa	24	DIN 53504
Elongation at break %	810	DIN 53504
Abrasion mm <sup>3</sup>	80	DIN 53516
Compression set at 70°C for 22 hours %	30	DIN 53517

Thickness (mm)	No. of insertions	Width (mtr)	Length (mtr)	Article no.
2	0	1,40	10	Abrasuper40 2/0
3	0	1,40	10	Abrasuper40 3/0
4	0	1,40	10	Abrasuper40 4/0
5	0	1,40	10	Abrasuper40 5/0
6	0	1,40	10	Abrasuper40 6/0
8	0	1,40	5	Abrasuper40 8/0
10	0	1,40	5	Abrasuper40 10/0
30	0	1,40	5	Abrasuper40 30/0

Quality rubber solutions





**Rubber Europe**

Thickness Tolerances		
Over (mm)	Upto (mm)	Tolerance +/- (mm)
0.5	2	0.2
2	3	0.3
3	6	0.4
6	10	0.5
10	15	0.8
15	25	1.0

Roll length Tolerances	
Length (mm)	Tolerance +/- (mm)
1.000	50
5.000	250
10.000	500
20.000	1.000

Roll width Tolerances	
length (mm)	Tolerance +/- (mm)
900	18
1.000	20
1.220	24
1.300	26
1.400	28